



A 70 HINGED - PVC

ENERGY EFFICIENCY

Thermal Transmission Coefficient
 U_w from 0.9 (W/m²K)

Please consult typology, dimensions and glazing.

ACCOUSTIC INSULATION

Maximum glazing: **40 mm.**
 Maximum acoustic insulation: **Rw = 46 dB.**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

Class 4

Water tightness (UNE-EN 12208:2000):

Class E1800

Wind resistance (UNE-EN 12210:2000):

Class C5

Reference test window 1.23 x 1.48 m. 2 sashes.

SECTIONS	Frame 70 mm Sash 80 mm		
CLASIFICACIÓN	Profile thickness Class A ≥ 2.8 mm Weather Severe weather Impact Class II		
MAXIMUM DIMENSIONS	Width (L) = 1,200 mm Height (H) = 1,450 mm Window		
	Width (L) = 1,000 mm Height (H) = 2,150 mm Balcony		
	Width (L) = 1,000 mm Height (H) = 2,300 mm Door		
MAXIMUM WEIGHT/SASH	80 Kg Window	100 Kg Balcony	120 Kg Door
	GASKETS		
	EPDM double gasket		
OPENING POSIBILITIES			
INWARDS	Side hung, turn&tilt, parallel-tilt, tilt and bi-fold		
OUTWARDS	Side hung		
FINISHES	Optionally bicoloured White Coloured wrapping Wood-imitation wrapping		

Please consult maximum dimensions according to types.

