



# E 170 LIFT & SLIDE - PVC

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

**$U_w$  from 0.9 (W/m<sup>2</sup>K)**

Please consult typology, dimensions and glazing.

## ACCOUSTIC INSULATION

Maximum glazing: **40 mm.**

Maximum acoustic insulation: **Rw = 42 dB.**

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (UNE-EN 12207:2000):

**Class 4**

Water tightness (UNE-EN 12208:2000):

**Class 7A**

Reference test 3.5 x 2.5 m. 1 Sash + 1 Fix

SECTIONS	Frame 170 mm Sash 70 mm
CLASIFICACION	Profile thickness Class A $\geq 2.8$ mm Weather Severe weather Impact Class II
MAXIMUM DIMENSIONS	Width (L) = 3,000 mm Height (H) = 2,750 mm
MAXIMUM WEIGHT/SASH	300 Kg.

OPENING POSIBILITIES	Lift&slide door, 1, 2 and 4 sashes.
FINISHES	Optionally bicoloured White Coloured wrapping Wood-imitation wrapping

Please consult maximum dimensions according to types.

